## NSN 4720-01-394-6219

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-394-6219 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.620 inches **Minimum Inside Bending Radius:** 2.000 inches **End Application:** Wiggins lift co. Forklift **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end **Outer Covering Environmental Protection:** Oil resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 23.500 inches working

**Thread Series Designator:** 

Unf 2nd end

## NSN 4720-01-394-6219

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0