NSN 4720-01-394-6223

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-394-6223

Inread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.500 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response			
Outside Diameter:			
0.745 inches			
Minimum Inside Bending Radius:			
3.000 inches			
Exterior Color:			
Black			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
10000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
2500.0 pounds per square inch			
Thread Size:			
0.875 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
5000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Weatherproof			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
71.000 inches			
Media For Which Designed:			

Fuel/oil, hydrocarbon single response

NSN 4720-01-394-6223

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0