NSN 4720-01-394-6224

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-394-6224

2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.500 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response			
Outside Diameter:			
0.745 inches			
Minimum Inside Bending Radius:			
3.000 inches			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 2nd end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
12 1st end			
Burst Test Pressure:			
10000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
2500.0 pounds per square inch			
Thread Size:			
1.062 inches 1st end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
5000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Weatherproof			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
12.500 inches			
Media For Which Designed:			

Fuel/oil, hydrocarbon single response

NSN 4720-01-394-6224

Nonmetallic Hose Assembly - Page 2 of 2



T1	0!	D!	
Thread	Series	Design	ator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0