NSN 4720-01-394-8167



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-394-8167 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.664 inches **Minimum Inside Bending Radius:** 2.000 inches **End Application:** Wiggins lift co. Forklift **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer molded rubber, ethylene propylene **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:**

4500.0 pounds per square inch

Outer Covering Environmental Protection:

Outer Governing Environmental Frotootio

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

103.000 inches

Special Features:

This is a twinline hose assembly

NSN 4720-01-394-8167

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0