## NSN 4720-01-395-3454

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-395-3454

Round						
Thread Class:						
2b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.500 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response						
Outside Diameter:						
0.780 inches						
Minimum Inside Bending Radius:						
3.500 inches						
Exterior Color:						
Black						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Burst Test Pressure:						
12000.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided steel wire and outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
3000.0 pounds per square inch						
Thread Size:						
0.750 inches 2nd end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
6000.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Outer Covering Environmental Protection:						
Abrasion resistant and oil resistant and weatherproof						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
48.000 inches						

## NSN 4720-01-395-3454

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0