

View Online at <https://aerobasegroup.com/nsn/4720-01-395-7328>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.985 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

2.360 inches

Minimum Inside Bending Radius:

10.000 inches

End Application:

Lcac: landing craft air-cushion

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

1st layer polytetrafluoroethylene impregnated glass fiber and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

2.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Inside Surface Condition:

Convuluted

Measuring Method And Length:

60.000 inches

Special Features:

Convuluted polytetrafluoroethylene ptfe is laminated to woven glass cloth

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0