

View Online at <https://aerobasegroup.com/nsn/4720-01-395-8894>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.190 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.520 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Natural

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Vacuum In Torr:

28.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.0 feet

Special Features:

Used on the pt-2 manifold

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0