Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-395-9118

0	tional Change
	tional Shape:
Round	
Thread Cla	
3b 1st end	
Thread Di	
Right-hand	
Inside Dia	
0.313 inch	
Outside D	
0.672 inch	
	Inside Bending Radius:
4.000 inch	
Connectio	n Style:
Swivel nut	with compression sleeve 1st end
End Conn	ection Design:
Straight 2n	d end
End Fitting	g Component And Material:
Complete f	itting steel all ends
Fitting Co	mponent And Surface Treatment:
Complete f	itting cadmium 1st end
Connectio	n Type:
Unthreade	d external tube 2nd end
Second E	nd Relationship With First End:
Not identic	al
Burst Test	t Pressure:
9000.0 pou	unds per square inch
First End	Swivel Action Capability:
Not include	ed and the second se
Maximum	Operating Pressure:
2000.0 pou	unds per square inch
Thread Siz	ze:
0.562 inch	es 1st end
Seat Angle	9:
37.0 degre	es 1st end
Inside Sur	face Condition:
Smooth	
Measuring	y Method And Length:
-	hes excluding end fittings
	iameter Tube Accommodated:
0.375 inch	
Special Fe	
-	eying tube material-rubber



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0