NSN 4720-01-396-1379

Cross Sectional Shape:

37.0 degrees 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-396-1379

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-58.0 degrees fahrenheit single response and 302.0 degrees fahrenheit single response
Outside Diameter:
0.680 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Blue
End Application:
1730-01-309-1243
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nonskive
Second End Relationship With First End:
Identical
Burst Test Pressure:
16000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided steel wire err-100
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:

NSN 4720-01-396-1379

Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof and abrasion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches
Special Features:
Embossed layline
Media For Which Designed:
Fuel/oil, hydrocarbon single response and water single response and air single response
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No