

View Online at <https://aerobasegroup.com/nsn/4720-01-396-1382>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-58.0 degrees fahrenheit and 302.0 degrees fahrenheit single response

**Outside Diameter:**

0.680 inches

**Minimum Inside Bending Radius:**

2.500 inches

**Exterior Color:**

Blue

**End Application:**

1730-01-309-1243

**Connection Style:**

Swivel, external seat for gasket seal 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external tube 2nd end

**Features Provided:**

Nonskive

**Burst Test Pressure:**

16000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer molded rubber, synthetic and 3rd layer braided steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

4000.0 pounds per square inch

**Thread Size:**

0.562 inches 1st end

**Hydrostatic Test Pressure:**

8000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

50.000 inches

**Special Features:**

Embossed layline

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water and air single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0