Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-396-1383

,	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-58.0 degrees fahrenheit sin	gle response and 302.0 degrees fahrenheit single response
Outside Diameter:	
0.680 inches	
Minimum Inside Bending R	Radius:
2.500 inches	
Exterior Color:	
Blue	
Angle Between Rigid Elbo	w Fittings In Deg:
0.0	
End Application:	
1730-01-309-1243	
Connection Style:	
Swivel, plain 2nd end	
End Connection Design:	
Elbow 2nd end	
End Fitting Component Ar	nd Material:
Complete fitting steel all end	ls
Connection Type:	
Threaded internal tube 1st e	nd
Features Provided:	
Nonskive	
Second End Relationship	With First End:
Not identical	
Burst Test Pressure:	
16000.0 pounds per square	inch
First End Swivel Action Ca	apability:
Not included	
Layer Composition And Lo	ocation:
1st layer braided steel wire	err-100
Maximum Operating Press	sure:
4000.0 pounds per square in	nch
Thread Size:	
0.562 inches 1st end	

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
60.000 inches
Second End Swivel Action Capability:
Not included
Special Features:
Embosses layline
Media For Which Designed:
Fuel/oil, hydrocarbon single response and water single response and air single response
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0