## NSN 4720-01-396-1483

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-396-1483

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
0.937 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, synthetic and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.500 inches working
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4720-01-396-1483

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0