Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-396-1491

Cross S	ectional Shape:
Round	
Thread (Class:
3b 1st er	nd
Thread I	Direction:
Right-ha	nd 1st end
Inside D	iameter:
0.562 inc	ches
Tempura	ature Rating:
-65.0 deg	grees fahrenheit and 450.0 degrees fahrenheit single response
Outside	Diameter:
0.920 inc	ches
Connect	ion Style:
Swivel n	ut flare 2nd end
End Cor	nection Design:
Straight	1st end
Connect	ion Type:
Threade	d internal tube 1st end
Burst Te	est Pressure:
8000.0 p	ounds per square inch
Layer Co	omposition And Location:
1st layer	molded rubber, synthetic and outer layer braided corrosion resistant steel wire
Maximu	m Operating Pressure:
1500.0 p	ounds per square inch
Thread S	Size:
0.562 inc	ches 2nd end
Seat Ang	gle:
37.0 deg	rees 2nd end
Hydrost	atic Test Pressure:
3000.0 p	ounds per square inch
Flow An	gle:
90.0 deg	rees 2nd end
Inside S	urface Condition:
Smooth	
Measuri	ng Method And Length:
22.875 ir	nches working
Thread S	Series Designator:
Unjf 1st e	end
Shelf Lif	e:
N/a	
Unit Of I	Measure:

NSN 4720-01-396-1491

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

