## NSN 4720-01-396-5024

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-396-5024



**Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** 400.0 degrees fahrenheit single response **Outside Diameter:** Between 0.455 inches and 0.490 inches **Minimum Inside Bending Radius:** 2.500 inches **Exterior Color:** Natural **End Application:** 4935-01-364-3292 **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch Flow Angle:

Smooth

**Measuring Method And Length:** 

38.000 inches

45.0 degrees 2nd end
Inside Surface Condition:

## NSN 4720-01-396-5024

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	<b>Designator:</b>
--------	--------	--------------------

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0