Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-397-5390

oss Sectional Shape:
bund
read Class:
1st end
read Direction:
ght-hand 1st end
side Diameter:
250 inches
mpurature Rating:
0.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
itside Diameter:
040 inches
nimum Inside Bending Radius:
000 inches
onnection Style:
vivel nut flare 1st end
d Connection Design:
raight 1st end
onnection Type:
readed internal tube 1st end
irst Test Pressure:
000.0 pounds per square inch
yer Composition And Location:
t layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
aximum Operating Pressure:
00.0 pounds per square inch
read Size:
138 inches 1st end
at Angle:
.0 degrees 1st end
rdrostatic Test Pressure:
00.0 pounds per square inch
side Surface Condition:
nooth
easuring Method And Length:
.000 inches
edia For Which Designed:
el/oil, hydrocarbon single response
read Series Designator:
If 1st end
elf Life:
a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0