Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-397-5395

Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -4.00 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Thread elitermal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Thread Size: 0.925 inches 1st end Burst Test Pressure: 12000.0 pounds per square inch Thread Size: 0.925 inches 1st end Burst Test Pressure: 1200.0 pounds per square inch Thread Size: 0.925 inches 1st end Burst Test Pressure: 0.926 inches 1st end Burst Test Pressure: 0.927 indegrees 1st end Burst Test Pressure: 0.928 inches 1st end Burst Test Pressure: 0.929 inches 1st end Burst Test Pressure: <th></th>	
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Thread Ginternal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer Draided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 800.0 pounds per square inch Inside Surface Condition: Straight Steel Minimum Operating Pressure: 30.0 pounds per square inch Inside Surface Condition: Straight Steel Minimum Operating Pressure: 30.0 pounds per square inch Hydrostatic Test Pressure: 30.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Cross Sectional Shape:
21 ist end Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Dstyle: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 0.00.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smoth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response	
Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Thread di internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end	
Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 300.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 300.0 pounds per square inch Ligende steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 300.0 pounds per square inch Inside Size: 300.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	
Inside Diameter: 0.525 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	
0.625 inches Tempurature Rating: 440.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un f 1st end	
Tempurature Rating: 440.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	
40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threade internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un f1st end	
Outside Diameter: 0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fue/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Tempurature Rating:
0.940 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un f 1st end	-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un f 1st end	Outside Diameter:
4.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un f1st end	0.940 inches
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un f 1st end	Minimum Inside Bending Radius:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un f1st end	4.000 inches
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end	Connection Style:
Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Swivel nut flare 1st end
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	End Connection Design:
Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Straight 1st end
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end	Connection Type:
12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end	Threaded internal tube 1st end
Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Burst Test Pressure:
1st layer braided steel wire and outer layer molded rubber, synthetic Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	12000.0 pounds per square inch
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Layer Composition And Location:
3000.0 pounds per square inch Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	1st layer braided steel wire and outer layer molded rubber, synthetic
Thread Size: 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Maximum Operating Pressure:
0.625 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	3000.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	0.625 inches 1st end
Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Seat Angle:
6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	37.0 degrees 1st end
Inside Surface Condition: Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Hydrostatic Test Pressure:
Smooth Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	6000.0 pounds per square inch
Measuring Method And Length: 38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Inside Surface Condition:
38.600 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Smooth
Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	Measuring Method And Length:
Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end	38.600 inches
Thread Series Designator: Unf 1st end	Media For Which Designed:
Unf 1st end	Fuel/oil, hydrocarbon single response
	Thread Series Designator:
Shelf Life:	Unf 1st end
	Shelf Life:
N/a	N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0