NSN 4720-01-397-5772

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-397-5772

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches

Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:
1.078 inches

Minimum Inside Bending Radius:

6.500 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided steel wire and 2nd layer braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

121.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-397-5772

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0