NSN 4720-01-397-7845

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-397-7845

| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 0.190 inches |
| Tempurature Rating: |
| -50.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.300 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| End Application: |
| 1730-01-272-4402 |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 3000.0 pounds per square inch |
| Layer Composition And Location: |
| |
| Outer layer braided corrosion resistant steel wire |
| Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: |
| · |
| Maximum Operating Pressure: |
| Maximum Operating Pressure: 600.0 pounds per square inch |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 36.000 inches working |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 36.000 inches working Shelf Life: |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 36.000 inches working Shelf Life: N/a |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 36.000 inches working Shelf Life: N/a |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 36.000 inches working Shelf Life: N/a Unit Of Measure: |
| Maximum Operating Pressure: 600.0 pounds per square inch Thread Size: 0.250 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 36.000 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: |