---

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-398-3403

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.230 inches  |
| Tempurature Rating:   |
| -55.0 degrees fahrenheit single response and 204.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.380 inches  |
| Minimum Inside Bending Radius:  |
| 1.500 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 16000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer molded rubber, synthetic  |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.438 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 244.000 inches  |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response   |
| Thread Series Designator:   |
| Unjf 1st end  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 4720-01-398-3403

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

