Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-398-4594

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.438 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.672 inches
Minimum Inside Bending Radius:
3.500 inches
Connection Style: Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location: 1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
45.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end

NSN 4720-01-398-4594

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0