

View Online at <https://aerobasegroup.com/nsn/4720-01-398-8346>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

1.200 inches

Minimum Inside Bending Radius:

9.500 inches

Hose Or Tubing Specification/std Data:

Sae j517, 100r12, type a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

3930-01-373-3625

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

16000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer wrapped rubber, synthetic err-100

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

1.3125 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

711.0 millimeters

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0