NSN 4720-01-399-1830

Cross Sectional Shape:

Round

Unjf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-399-1830

Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.310 inches					
Tempurature Rating:					
-54.0 degrees fahrenheit single response and 204.0 degrees fahrenheit single response					
Outside Diameter:					
0.460 inches					
Minimum Inside Bending Radius:					
2.500 inches					
Connection Style:					
Swivel nut flare 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Nuts drilled for lockwire					
Burst Test Pressure:					
14000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
0.562 inches 2nd end					
Seat Angle:					
37.0 degrees 2nd end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Flow Angle:					
90.0 degrees 2nd end					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
35.125 inches working					
Thread Series Designator:					

NSN 4720-01-399-1830

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0