Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-399-4293

Cross	Sectional	Shape:
Round		

**Thread Class:** 

3b 1st end

# **Thread Direction:**

Right-hand 1st end

# Inside Diameter:

0.875 inches

### **Tempurature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

### **Outside Diameter:**

1.156 inches

Minimum Inside Bending Radius:

#### 5.500 inches

**Exterior Color:** 

Natural

## Angle Between Rigid Elbow Fittings In Deg:

0.0

## **Connection Style:**

Swivel nut flare 2nd end

# End Connection Design:

Straight 1st end

### **Connection Type:**

Threaded internal tube 1st end

# Features Provided:

Reusable end fittings

#### **Burst Test Pressure:**

2500.0 pounds per square inch

## Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

## Maximum Operating Pressure:

750.0 pounds per square inch

**Thread Size:** 

1.312 inches 2nd end

### Seat Angle:

37.0 degrees 2nd end

## Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

# Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



# Measuring Method And Length:

72.000 inches

# Media For Which Designed:

Fuel/oil, hydrocarbon single response

# Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A542a0