Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-399-5682

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction:
Thread Class: 2b 1st end
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.860 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and outer layer braided polyester cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.750 inches
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

