Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-400-0540

Cross Sectional Shape: Round Thread Class: 2b 2nd end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Outside Diameter: 0.625 inches End Application: 2350-01-163-1437 Connection Style: Swivel nut flare 2nd end End Connection Oresign: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Thread Class:2b 2nd endThread Direction:Right-hand 1st endInside Diameter:0.250 inchesOutside Diameter:0.625 inchesEnd Application:2350-01-163-1437Connection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
2b 2nd end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Outside Diameter: 0.625 inches End Application: 2350-01-163-1437 Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smoth Measuring Method And Length: 8.000 inches Media For Which Designed: Fue/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Right-hand 1st endInside Diameter:0.250 inchesOutside Diameter:0.625 inchesEnd Application:2350-01-163-1437Connection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
Right-hand 1st endInside Diameter:0.250 inchesOutside Diameter:0.625 inchesEnd Application:2350-01-163-1437Connection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oll, hydrocarbon single responseThread Series Designator:Unf 2nd end
Inside Diameter:0.250 inchesOutside Diameter:0.625 inchesEnd Application:2350-01-163-1437Connection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
Outside Diameter:0.625 inchesEnd Application:2350-01-163-1437Connection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
0.625 inches End Application: 2350-01-163-1437 Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
End Application:2350-01-163-1437Connection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
2350-01-163-1437 Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
2350-01-163-1437 Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
Swivel nut flare 2nd endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Connection Type:Threaded internal tube 1st endLayer Composition And Location:Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
Threaded internal tube 1st end Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end 17.0 degrees 2nd end 17.0 degrees 2nd end 18.000 inches 18.000 inches 19.000 inches 10.000 inches 10.0000 inches 10.000 inches 10.000 inche
Outer layer molded rubber, syntheticThread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
Thread Size:0.438 inches 2nd endSeat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
0.438 inches 2nd end Seat Angle: 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Seat Angle:37.0 degrees 2nd endInside Surface Condition:SmoothMeasuring Method And Length:8.000 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Unf 2nd end
 37.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Smooth Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Measuring Method And Length: 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end
Thread Series Designator: Unf 2nd end
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0