## NSN 4720-01-406-1956

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-406-1956

Cross Sectional Shape
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.609 inches
End Application:
2350-00-808-7100
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon and air single response
Thread Series Designator:
Unf 1st end
Shelf Life:

## NSN 4720-01-406-1956

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0