NSN 4720-01-406-3556

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-406-3556 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response **Outside Diameter:** 1.109 inches **Minimum Inside Bending Radius:** 7.380 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch **Vacuum In Torr:** 28.0 **Inside Surface Condition:**

Smooth

Measuring Method And Length:

30.500 inches

NSN 4720-01-406-3556

Nonmetallic Hose Assembly - Page 2 of 2



| | | • | | |
|----|------|--------|--------|--------|
| Ιh | read | Series | Desiar | າator: |
| | | | | |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0