

View Online at <https://aerobasegroup.com/nsn/4720-01-406-3560>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

1.109 inches

Minimum Inside Bending Radius:

7.380 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

0.0

End Application:

Helicopter, mh-53e; helicopter, ch-53a/d/e

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

28.0

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.000 inches

Special Features:

Flight safety critical

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0