Nonmetallic Hose Assembly - Page 1 of 2



, ,
View Online at https://aerobasegroup.com/nsn/4720-01-406-4715
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.780 inches
Minimum Inside Bending Radius:
3.750 inches
Exterior Color:
Natural
End Application:
2350-01-369-6082
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
750.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Vacuum In Torr:
10.0
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 15.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A542a0