NSN 4720-01-406-6157

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-406-6157 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.625 inches **Minimum Inside Bending Radius:** 3.000 inches **End Application:** 4935-01-364-3292 **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 8000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 31.500 inches **Thread Series Designator:**

Unf 1st end Shelf Life:

N/a

NSN 4720-01-406-6157

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0