

View Online at <https://aerobasegroup.com/nsn/4720-01-406-7477>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.500 inches

**Minimum Inside Bending Radius:**

2.500 inches

**End Application:**

2350-01-369-6083: carrier, smoke generator

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

1250.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fabric and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

300.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

625.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

131.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water single response

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

96906-ms53204 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0