Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-407-2945

С	cross Sectional Shape:
R	Round
т	hread Class:
3	b 1st end
т	hread Direction:
R	light-hand 1st end
lr	nside Diameter:
0	.406 inches
т	empurature Rating:
-6	65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
0	Dutside Diameter:
0	.760 inches
N	Iinimum Inside Bending Radius:
1	.750 inches
Е	and Application:
2	320-01-383-3850
С	Connection Style:
S	Swivel nut flare 1st end
Е	Ind Connection Design:
S	Straight 1st end
С	Connection Type:
т	hreaded internal tube 1st end
F	eatures Provided:
R	Reusable end fittings
В	Burst Test Pressure:
4	000.0 pounds per square inch
L	ayer Composition And Location:
1	st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated fabric
N	faximum Operating Pressure:
1	000.0 pounds per square inch
т	hread Size:
0	.750 inches 1st end
S	eat Angle:
3	7.0 degrees 1st end
Н	lydrostatic Test Pressure:
2	000.0 pounds per square inch
0	Duter Covering Environmental Protection:
С	Dil resistant
Ir	nside Surface Condition:
S	Smooth
N	leasuring Method And Length:
2	4.000 inches

NSN 4720-01-407-2945 Nonmetallic Hose Assembly - Page 2 of 2

Special Features: End caps for shipping required Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

