NSN 4720-01-407-2946

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-407-2946

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.760 inches
Minimum Inside Bending Radius:
1.750 inches
End Application:
2320-01-383-3850
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated fabric
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:

Smooth

NSN 4720-01-407-2946

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 32.750 inches working Special Features: End caps for shipping required Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A542a0