NSN 4720-01-407-3567

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-407-3567

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.187 inches
Minimum Inside Bending Radius:
5.500 inches
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.562 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
34.000 inches working
Thread Series Designator:

Un 2nd end

NSN 4720-01-407-3567

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0