Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-407-9280

	De:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.313 inches	
Tempurature Rating:	
	eit single response and 450.0 degrees fahrenheit single response
Outside Diameter:	
0.469 inches	
Minimum Inside Ben	ding Radius:
4.000 inches	
End Application:	
Aircraft, lockheed aer	pnautical system, model ac130a/h/u
Connection Style:	
Swivel nut, flareless 1	
End Connection Des	gn:
Straight 1st end	
Connection Type:	
Threaded internal tube	1st end
Burst Test Pressure:	
9000.0 pounds per sq	are inch
Layer Composition A	nd Location:
Outer layer braided co	rrosion resistant steel wire
Maximum Operating	Pressure:
1500.0 pounds per sq	lare inch
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pre	ssure:
3000.0 pounds per sq	lare inch
Outer Covering Envi	onmental Protection:
Acid resistant and alco	hol resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant and solvent
resistant	
Inside Surface Cond	tion:
Smooth	
Measuring Method A	nd Length:
24.000 inches	
Thread Series Design	nator:
Unjf 1st end	

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

96906-ms8006 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0