## NSN 4720-01-408-1545



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-408-1545 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** Between 0.714 inches and 0.760 inches **Minimum Inside Bending Radius:** 1.750 inches **End Application:** 2320-01-383-3850 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 4000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant **Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

72.500 inches

**Thread Series Designator:** 

Unjf 1st end

## NSN 4720-01-408-1545

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0