Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-408-3182

| С | ross Sectional Shape: |
|----|---|
| R | ound |
| Т | hread Class: |
| 3 | b 1st end |
| т | hread Direction: |
| R | ight-hand 1st end |
| Ir | nside Diameter: |
| 0 | 188 inches |
| Т | empurature Rating: |
| -6 | 5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| 0 | utside Diameter: |
| 0 | .343 inches |
| M | linimum Inside Bending Radius: |
| 1 | .500 inches |
| Ε | nd Application: |
| A | c130a/h/u aircraft, lockheed corp |
| С | onnection Style: |
| S | wivel nut flare 2nd end |
| Ε | nd Connection Design: |
| S | traight 1st end |
| С | onnection Type: |
| Т | hreaded internal tube 1st end |
| В | urst Test Pressure: |
| 1: | 2000.0 pounds per square inch |
| L | ayer Composition And Location: |
| 0 | uter layer braided corrosion resistant steel wire |
| N | laximum Operating Pressure: |
| 1 | 500.0 pounds per square inch |
| т | hread Size: |
| 0 | 438 inches 1st end |
| S | eat Angle: |
| 3 | 7.0 degrees 2nd end |
| н | ydrostatic Test Pressure: |
| 3 | 000.0 pounds per square inch |
| F | low Angle: |
| 9 | 0.0 degrees 2nd end |
| Ir | side Surface Condition: |
| S | mooth |
| M | leasuring Method And Length: |
| 1 | 9.000 inches working |
| т | hread Series Designator: |
| U | nf 2nd end |

Nonmetallic Hose Assembly - Page 2 of 2

Specification Data:

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

