## NSN 4720-01-409-2537



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-409-2537 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.688 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.219 inches **Minimum Inside Bending Radius: 7.750** inches **End Application:** 2320-01-123-1608 **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3000.0 pounds per square inch

**Thread Size:** 

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

**Hydrostatic Test Pressure:** 

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

74.000 inches working

## NSN 4720-01-409-2537

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0