Nonmetallic Hose Assembly - Page 1 of 2



response

View Online at https://aerobasegroup.com/nsn/4720-01-411-4204

| View Online at https://aerobasegroup.com/nsn/4720-01-411-4204                 |
|---|
| Cross Sectional Shape:  |
| Round   |
| Thread Class:   |
| 2a 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.250 inches  |
| Tempurature Rating:   |
| -100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single |
| Outside Diameter:   |
| 0.359 inches  |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| Connection Style:   |
| Swivel nut, inverted flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external tube 2nd end  |
| Thready Qty Per Inch (tpi):   |
| 24 2nd end  |
| Burst Test Pressure:  |
| 10000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                            |
| Maximum Operating Pressure:   |
| 1500.0 pounds per square inch   |
| Thread Size:  |
| 0.438 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 2nd end  |
| Flow Angle:   |
| 45.0 degrees 2nd end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 24.000 inches working   |
| Special Features:   |
| Brake hose assembly   |
| Thread Series Designator:   |
| Un 2nd end  |
|   |

## NSN 4720-01-411-4204

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

