NSN 4720-01-411-8414

Cross Sectional Shape:

Inside Diameter: 4.050 inches

Tempurature Rating:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-411-8414

410.0 degrees fahrenheit single response
Bolt Circle Diameter:
6.562 inches 1st end
Flange Thickness:
0.500 inches 1st end
Outside Diameter:
4.500 inches
Minimum Inside Bending Radius:
24.000 inches
Bolt Hole Quantity:
8 1st end
Flange Outside Diameter:
7.688 inches 1st end
Connection Style:
Raised swivel 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Raised Face Diameter:
4.281 inches 1st end
End Flange Construction:
End Flange Construction: Solid 1st end
_
Solid 1st end
Solid 1st end End Connection Design:
Solid 1st end End Connection Design: Straight 1st end
Solid 1st end End Connection Design: Straight 1st end Connection Type:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Vacuum In Torr:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Vacuum In Torr: 50.8

NSN 4720-01-411-8414

A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
80.620 inches
Flange Style:
Round w/ bolt holes 1st end
Special Features:
Two hose assemblies connected by a 90 degrees elbow; first and second leg lengths identical
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: