NSN 4720-01-411-8418

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-411-8418

Roulid
Inside Diameter:
4.050 inches
Tempurature Rating:
410.0 degrees fahrenheit single response
Bolt Circle Diameter:
6.562 inches 2nd end
Flange Thickness:
0.500 inches 2nd end
Outside Diameter:
4.500 inches
Minimum Inside Bending Radius:
24.000 inches
Bolt Hole Quantity:
8 2nd end
Flange Outside Diameter:
7.688 inches 2nd end
Connection Style:
Raised swivel 2nd end
Bolt Hole Diameter:
0.562 inches 2nd end
Raised Face Diameter:
Raised Face Diameter: 4.281 inches 2nd end
4.281 inches 2nd end
4.281 inches 2nd end End Flange Construction:
4.281 inches 2nd end End Flange Construction: Solid 2nd end
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design:
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type:
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided:
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support Burst Test Pressure:
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location:
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch
4.281 inches 2nd end End Flange Construction: Solid 2nd end End Connection Design: Straight 1st end Connection Type: Raised face flange 2nd end Features Provided: Internal support Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Flow Angle:

NSN 4720-01-411-8418

A542a0

Nonmetallic Hose Assembly - Page 2 of 2

