

View Online at <https://aerobasegroup.com/nsn/4720-01-411-8491>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

2.250 inches

Minimum Inside Bending Radius:

10.000 inches

Exterior Color:

Natural

End Application:

2350-00-808-7100

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer braided fiber and 2nd layer braided fiber and 3rd layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

1.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.750 inches and 25.250 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0