

View Online at <https://aerobasegroup.com/nsn/4720-01-412-2682>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.190 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.520 inches

Minimum Inside Bending Radius:

3.000 inches

End Application:

Mk-48 torpedo system, westinghouse electric corp.

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided steel wire and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.000 feet working

Special Features:

Label-stamped caution air/nitrogen 2000 psi 4 places; with clamp, part no.Da82919; lanyard assembly, ca82920-2; o-ring, 3-904; connector 4fsx-ss; cable cl3-c-7.0; ferrules 4ea.Cl-3f

Media For Which Designed:

Fuel/oil, hydrocarbon and nitrogen, gaseous single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0