NSN 4720-01-413-2572

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-413-2572

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.485 inches and 0.531 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.846 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.812 inches 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and waterproof

Unjf 1st end

Smooth

Inside Surface Condition:

Measuring Method And Length:

Fuel/oil, hydrocarbon single response

Media For Which Designed:

Thread Series Designator:

550.0 millimeters working and 570.0 millimeters working

NSN 4720-01-413-2572

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0