

View Online at <https://aerobasegroup.com/nsn/4720-01-413-4058>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

1.109 inches

Minimum Inside Bending Radius:

7.375 inches

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nuts drilled for lockwire

Thready Qty Per Inch (tpi):

14 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

1.250 inches 2nd end

Seat Angle:

8.5 degrees 2nd end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Acid resistant and alcohol resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant and solvent resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.300 inches working

Thread Series Designator:

Unjs 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0