NSN 4720-01-413-4068

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-413-4068

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.490 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.700 inches |
| Minimum Inside Bending Radius: |
| 3.250 inches |
| Exterior Color: |
| Orange or red |
| End Application: |
| Helicopter, carrier based asw, sh-60f; next higher assembly reeling machine, cable, motor driven |
| Connection Style: |
| Swivel nut, flareless 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.875 inches 2nd end |
| Seat Angle: |
| 12.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |

27.500 inches working

NSN 4720-01-413-4068

Nonmetallic Hose Assembly - Page 2 of 2



| | | _ |
|--------|----------|-------------|
| Thread | l Series | Designator: |
| | | |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0