Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-413-6037

| ~ | |
|----|--|
| | ross Sectional Shape: |
| | ound |
| | hread Class: |
| | b 1st end |
| | nread Direction: |
| | ight-hand 1st end |
| | side Diameter: |
| - | 335 inches |
| | empurature Rating: |
| 50 | 0.0 degrees celsius single response |
| 0 | utside Diameter: |
| - | 610 inches |
| Mi | inimum Inside Bending Radius: |
| 1. | 000 inches |
| Er | nd Application: |
| Se | eawolf class ssn, an/bsy- (v) -trident submarine |
| Co | onnection Style: |
| S١ | wivel nut flare 1st end |
| Er | nd Connection Design: |
| St | traight 1st end |
| Co | onnection Type: |
| T٢ | nreaded internal tube 1st end |
| В | urst Test Pressure: |
| 10 | 000.0 pounds per square inch |
| La | ayer Composition And Location: |
| 1s | st layer braided polyester cord and outer layer braided polyamide cord |
| M | aximum Operating Pressure: |
| 25 | 50.0 pounds per square inch |
| Tł | nread Size: |
| 0. | 562 inches 1st end |
| Se | eat Angle: |
| 37 | 7.0 degrees 1st end |
| Hy | ydrostatic Test Pressure: |
| 50 | 00.0 pounds per square inch |
| In | side Surface Condition: |
| Sr | nooth |
| M | easuring Method And Length: |
| 25 | 5.000 inches working |
| Tł | nread Series Designator: |
| Ur | njf 1st end |
| Sł | helf Life: |
| N/ | 'a |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0