Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-413-8226

Cross Sectional Shape:	
Round	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response	
Outside Diameter:	
0.970 inches	
Minimum Inside Bending Radius:	
7.000 inches	
Quick Disconnect Size:	
0.500 inches 2nd end	
End Application:	
2350-01-390-4683	
Connection Style:	
Push (internal) 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Internal quick disconnect 1st end	
Burst Test Pressure:	
17000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided wire and 2nd layer braided wire and outer layer molded rubbe	er, synthetic
Maximum Operating Pressure:	
4300.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
144.000 inches	
Special Features:	
Includes: adapter 2, plug 1, cap 1, bandmarker 5	
Media For Which Designed:	
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A542a0	