

View Online at <https://aerobasegroup.com/nsn/4720-01-414-0334>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.406 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.770 inches

**Minimum Inside Bending Radius:**

1.500 inches

**End Application:**

Forklift truck, wiggins lift co. Inc, model no. 15k

**Connection Style:**

Plain 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided polyester cord and 2nd layer braided polyester cord and outer layer polyester

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

14.710 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unj 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0