Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-414-0413

Cross Sectional Shape:
Round
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
8.000 inches
Exterior Color:
Black
Quick Disconnect Size:
0.625 inches 1st end
Connection Style:
Cam (external) 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Universal quick disconnect 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire err-100
Maximum Operating Pressure:
500.0 pounds per square inch
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches
Special Features:
Inner conveying tube material-plastic, polyamide
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Na

No

NSN 4720-01-414-0413

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

